

Section I. Product Identification and Uses

		HMIS (HFRP)	
		Health Hazard	1
		Fire Hazard	4
		Reactivity	0
		Personal Protection	x
Common / Trade name	HARVEST TIME Country Garden	TDG	Class 2.1
WHMIS	A, B5, D2B	PIN	UN1950 AEROSOLS
Code	1222	PG	X
Material uses	Other non specified industry: AIR FRESHENER		

Section II. Hazardous Ingredients

Name	CAS #	% by weight	TLV/PEL	LC50/LD50
Isopropyl alcohol	67-63-0	45 - 55	Not available.	ORAL (LD50): Acute: 3600 mg/kg [Mouse.], > 4720 mg/kg [Rat].
Dimethyl methane	74-98-6	15 - 25	Simple asphyxiant.	Not available.
Trimethyl methane	75-28-5	15 - 25	Not available.	Not available.
Tryethylene glycol	112-27-6	1 - 5	Not available.	Not available.

Section III. First Aid Measures

Eye contact	Flush with plenty of water for at least 15 minutes, If irritation persists, seek medical attention.
Skin contact	Gently and thoroughly wash the skin with running water and non-abrasive soap. Consult physician if irritation persists.
Inhalation	Allow the victim to rest in a well-ventilated area.If discomfort persists seek medical attention.
Ingestion	Do not induce vomiting. Have conscious person drink several glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

Section IV. Physical Data

Physical state and appearance	Aerosol.	Colour	Not available.
pH (1% soln/water)	Not applicable.	Odour	Fragrance like.
pH (concentrate)	Not available.	Volatility	Not available.
Boiling point	Not available.	Vapour density	The highest known value is 5.17 (Air = 1) (Tryethylene glycol). Weighted average: 2.25 (Air = 1)
Specific gravity	0.8 (Water = 1)	Vapour pressure	0.689294 kPa (5.2 mm Hg) (at 20°C)
Solubility	Easily soluble in cold water, hot water, methanol, diethyl ether.		

Section V. Fire and Explosion Data

The product is	Flammable.
Auto-ignition temperature	Not available.
Flash points	The lowest known value is Closed cup: 11.67°C (53°F). Open cup: 18.3°C (64.9°F). (Cleveland). (Isopropanol)
Degradation products	carbon oxides (CO, CO ^{L2^n})
Extinguishing media	SMALL FIRE: Use DRY chemicals, CO ₂ , water spray or foam. LARGE FIRE: Use water spray, fog or foam. DO NOT use water jet.

Section VI. Reactivity data

Stability	The product is stable.
Decomp. products	See fire degradation products.
Reactivity	Incompatible with oxidizing material, acids, alkalis and chlorinated compounds.

Section VII. Toxicological properties

Route of entry	Ingestion. Inhalation Skin
Toxicity for animals	See section II
Acute effects	Isopropanol is irritating and possibly injurious to the eyes if not removed promptly. Frequent and prolonged contact with skin may irritate and cause dermatis. Vapor concentration are irritating to the respiratory tract and may have other central nervous system effects.
Chronic	CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL

effects TOXICITY: Not available. Repeated or prolonged exposure to the substance can produce target organs damage. Prolonged exposure may cause skin and eye chronic irritation.

Section VIII. Preventive measure

Waste disposal Do not puncture or incinerate containers, even when empty. Dispose of in accordance with local and federal regulations. Recycle, if possible.

Storage Compressed gases should be stored in a separate safety storage cabinet or room. Store in a cool, well ventilated area not to exceed 50 deg. C.

Precautions Keep away from heat. Keep away from sources of ignition. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If you feel unwell, seek medical attention and show the label when possible. Keep container tightly closed and in a well-ventilated place.

Spill and leak If container is ruptured or begins to leak, place in a well-ventilated area free of spark and ignition sources. Any remaining liquid should be collected with absorbent media. Dispose of this material and its container at hazardous or special waste collection point.

Section IX. Personal protective equipment

Gloves Not required - Avoid contact with skin.

Respiratory Not required - Avoid breathing vapors or spray mists.

Eyes Safety glasses recommended when installing new container to avoid possible contact with eyes.

Other No additional remark.

Eng. controls Ventilation is normally required when handling or using this product.

Section X. Preparation and other Information

Validated by the Regulatory Affairs Department on 16 June 2005

Printed 17 June 2005

CANUTEC : (613) 996-6666

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex A. Legend

HMIS Hazardous Materials Identification System

WHMIS WHMIS Workplace Hazardous Materials Information System

TDG Transport Dangerous Goods

PIN Product Identification Number

PG Packaging Group
